

### GV Egon VAC



#### Standardowe wyposażenie:

- 5.211.0090 
- 3.753.0127 
- 6.402.0071 
- 3.754.0204 
- 3.754.0121 
- 3.754.0256 
- 3.754.0255 
- 3.754.0005 
- 3.754.0271 
- 3.754.0196 
- 3.754.0215 
- 3.754.0197 
- 3.754.0109 
- 3.754.0108 
- 3.754.0110 
- 3.754.0257 
- 6.402.0105 
- 3.752.0123 
- 3.754.0175 
- 3.099.1108 

#### Wyposażony w:

- Wskaźnik pary • Zbiornik ze stali nierdzewnej AISI 304 • Wskaźnik niskiego poziomu wody • Filtr zmywalny • Wąż 2m • 8l zbiornik na wodę • Koła odpowiednie do przemysłu żywnościowego • Przełącznik z kontrolką • Filtr wody • Manometr glicerynowy

#### Certyfikat TUV do użytku profesjonalnego

GV Egon VAC	
kod	8.406.0015
max. ciśnienie pary/temperatura	5 bar/152° C
pobór mocy/napięcie	1900 W/220/240V ~ 50Hz (Ph 1)
produkcja pary	1200 (max 1400) W
typ zbiornika/pojemność	24 kPa/220 m³/h
pojemność zbiornika wody/detergentu	8 l