

# RAPID 15 M 38 C/BC/Long Run

The small walk behind scrubber dryer Rapid 15, has been further improved in its structural features and functionalities.

A complete set of combined solutions makes Rapid 15 suitable for any cleaning task in small-medium areas. Rapid 15 distinctive feature is flexibility. The front knob allows the user to adjust the brush incidence to the floor, so ensuring a perfect adherence to every working surface with every accessory, for excellent cleaning results.

The practical external wheel allows an easy height adjustment of the brush head, preventing any overload of the brush motor. So Rapid 15 can work successfully everywhere. The squeegee system perfectly covers the water track in any condition, for excellent drying results. And the new pedal lifting system makes it today even more comfortable for the user and reliable. Innovative features that, together with the compact dimensions and the long battery life and running time (up to 2 hours in the Long Run version, with XFC batteries), make Rapid 15 the perfect solution for every environment and surface, above all in narrow spaces.



External wheel adjustable pressure



Squeegee and rotation



XFC batteries (Long Run version)



New squeegee lifting system with pedal



Removable lid + floating ball + filter



Adjustable handle

## PRODUCT IDENTIFICATION

Type	Ref. No.	Pieces / pallet
<b>RAPID 15 M 38 C</b>	11.0050.01	<b>1</b>
<b>RAPID 15 M 38 BC</b>	13.0050.01	<b>1</b>
<b>RAPID 15 M 38 BC Long Run</b>	13.0070.01	<b>1</b>

## TECHNICAL DATA

FEATURES			TRACTION		
Cleaning width	mm	385	Motor rating	W	---
Squeegee width	mm	450	Driving speed	km / h	---
Performance (theoretical-practical)	m <sup>2</sup> / h	1.540-920	Hill climbing ability	%	2
Power supply		Battery 24V	VACUUM		
Installed power	W	510	Motor rating	W	250
Advancement		Manual	Vacuum	mbar/mm H2O	68 / 700
BRUSHES			Airflow rating	l / sec	28
Diameter - pad x No.	mm-inch x nr	385 - 15" x 1	Noise level	dB(A)	65
Motor rating x No.	W x nr	260 x 1	TANK Type		
Motor speed	rpm	130	Cleaning solution tank	l	15
Down pressure - Contact pressure	kg - gr / cm <sup>2</sup>	25,5 - 32,4	Recovery tank	l	16
			DIMENSIONS ( l x w x h )		
				mm	865x430x1100
			WEIGHT (empty / with batteries)		
				kg	40

## STANDARD ACCESSORIES

## OPTIONAL ACCESSORIES

Type	Ref. No.	Type	Ref. No.
15" Polipropylene brush ø 0,7	40.0008.00	15" Polypropylene brush soft ø 0,5	40.0408.00
Filling hose	30.0024.00	15" Polypropylene brush ø 0,9	40.0108.00
Front Polyurethane blade	39.0070.00	15" tynex brush grit 240 - ø 0,9	40.0208.00
Rear Polyurethane blade	39.0071.00	Pad holder 355 mm (for 15" Pad)	40.1008.00
On board battery charger 24V 5A (Shuko plug 220-240V)**/**	18.0032.00	Front rubber blade	39.0077.00
Batteries set (2 pcs) 12V 25Ah Gel**	18.0017.01	Rear rubber blade	39.0078.00
External battery charger 24V 30A (Shuko plug IP44 220-240 VAC)**/**	18.0029.00	Splashguard with bristles	95.0088.00
Battery set (2 pcs) XFC 12V 35 Ah Gel***	18.0030.00		

\*Only for C versions - \*\*Only for BC version - \*\*\*Only for BC Long Run version